





Kindermann **Klick** & Show

Wireless Presentation System for small to mid-sized meeting rooms, classrooms and huddle spaces


Meeting Room



Huddle Space



Classroom





Kindermann **Klick & Show**

Wireless Presentation System for small to mid-sized meeting rooms, classrooms and huddle spaces

The Kindermann **Klick & Show** presentation system allows users to share content from their laptops or mobile devices in a very simple way – with no configuration, no cables and without wasting time.



BYOD Collaboration – simple and secure

Its simple operation makes Kindermann Klick & Show the right choice for enterprise-wide deployment in meeting rooms and huddle spaces or in educational facilities or seminar hotels. You can rest assured that your content is secured while being transmitted wirelessly, due to the implementation of security standards.

Kindermann Klick & Show is available as a kit, containing the K-10S base unit and two Klick & Show TOUCH transmitters, but also as the K-10L software-only version without TOUCH transmitters.

Additional transmitters can be purchased as an option for both versions.

The Klick & Show TOUCH transmitter is a compact WiFi sender, coming in a sleek design of an easy-to-use touch-sensitive dongle, which is connected to the laptop via USB. Klick & Show TOUCH is the easy-to-use approach to collaborative meetings.

Touch & Go

Using Kindermann Klick & Show you can collaborate with other meeting participants, including guests, and present audio-visual content, even without any training.

Windows and Mac laptop users simply connect the Klick & Show TOUCH Transmitter to a USB port of their device. With a short touch on the sensor button your live laptop content is mirrored to the main display device.

The dongle features a dual-color LED indicator and „force-feedback“ vibration to provide feedback about the activity status to the user.

Alternatively, a pure software-based connection is possible, using the laptop's internal WiFi antenna instead of the TOUCH transmitter.

Users of Apple or Android mobile devices can download the free app to share their content – or use the built-in Airplay function instead (for iOS devices only).

Wired content, e.g. from a PC or DVD player, can be presented using the HDMI input port on the Klick & Show base unit - even 4K compatible on the K-10S.

The Kindermann Klick & Show product family

Standard-version

Klick & Show K-10S Kit

including 1 x K-10S base unit and 2 x TOUCH sensor-transmitters. Additional transmitters are available as an option.

Simply connect the Klick & Show TOUCH transmitter to your Windows or Mac laptop to mirror content to the main display device with a touch on the sensor button.

Users of Apple or Android mobile devices can download the free app to share content (Airplay for iOS devices).



Klick & Show K10S Kit

7488 000 300

Lite-version

Klick & Show K-10L

including 1 x K-10L base unit. For use with Universal PC-Client and laptop Wifi. TOUCH transmitters available as an add-on.

Simply run the Klick & Show Universal PC-Client software on your laptop, which is available for download from www.KlickandShow.com or from the base unit, to mirror content.

Users of Apple or Android mobile devices can download the free app to share content (Airplay for iOS devices).



Klick & Show K10L

7488 000 305

Klick & Show TOUCH Sensor-Transmitter

Compact, sleek design WiFi sender, with touch-sensitive surface, vibration feedback and USB 2.0 connection.

Single add-on transmitter for the K-10S standard kit or the K-10L Lite version.




Klick & Show TOUCH Sensor-Transmitter

7488 000 301

All-in-One Software

Klick & Show Universal PC-Client for K-10S Kit and K-10L

All-in-One PC-Client, for desktop mirroring using the laptop's on-board WiFi or the Klick & Show TOUCH transmitter.



Klick & Show Tray

Holds up to 4 Klick & Show TOUCH transmitters.

Its sleek design, matching the shape of the TOUCH dongles, blends well with modern and classical meeting room interior.

Constructed from high-quality plastic with machined aluminium socket plate and felt pads.



Klick & Show Tray

7488 000 303

Klick & Show Type-C Cap

USB type-C adapter cap for using a TOUCH transmitter on a PC/Mac's USB-C port.

Fitted with an elastic strap, the type-C adapter can be permanently fastened to the transmitter.



Klick & Show Type-C Cap

7488 000 304



Kindermann Klick & Show Features

PC/Mac compatible

Wireless transmission for Microsoft Windows or Apple Mac laptops and PCs, either using the Klick & Show TOUCH transmitter or laptop WiFi.

iOS & Android App

Free apps, for wireless content sharing from iOS/Android mobile devices, remote-view and more.

Airplay

Supports „Airplay“ for wireless content mirroring from iOS devices, without using an app.

Mirror/Extend

Choose between mirroring your primary or secondary laptop desktop for perfect Powerpoint presentations with preview functionality.

Low-Latency 1080p

Wireless, smooth transmission with high 1080P resolution and low latency < 130ms.

Fast-Switch

Fast switching between different sources in less than 1s.

USB-HID Touch

Built-in low-latency USB-HID function for connecting touch-displays and interactive boards.

PoE-Support

Optional simplified powering of the base unit via Power-over-Ethernet.

Security

AES WPA2PSK authentication protocol and Security-Level function for secure signal transmission.

Local Media Playback

Push videos, pictures and music to the Klick & Show base unit for perfectly smooth media-playback while using the Android or iOS app.

Whiteboarding & Annotations

Built-in whiteboarding & annotation tools for more productive meetings.

Remote-View

Allows remote-viewing of the active signal on the participant's mobile device.

Presenter-Lock

Prevents unauthorized activation of the „Remote-View“ function.

Remote-Mouse

Allows mouse cursor control of the presenter's PC or Mac laptop by using a mobile device just like a gyroscope mouse.

Wireless-AP & LAN-Network

Dual-Network function, with built-in fast IEEE 802.11n/ac wireless access point and additional wired Ethernet LAN port for separate routing and internet access for guests and employees in a corporate network environment.

WiFi-Analyzer

Built-in WiFi-Analyzer tool for easy setup.

HDMI 2.0 Out

Powerful built-in HDMI 2.0 scaling-engine for high resolution 4K/60 Hz signal output to large-format Ultra-HD 4K displays (K-10S only, K-10L up to 1080P/WUXGA).

Aux HDMI-In

Auxiliary HDMI input for external wired sources like document camera, DVD or wired laptop. Compatibility up to 4K/60 Hz for K-10S, up to 1080P/WUXGA for K-10L.

Analog Audio Out/In

For audio output over external amplifier/ speakers in larger rooms and for analog audio embedding on the HDMI input.

Firmware-Upgrade

Future-proof due to simple firmware-upgrade via local USB port or LAN/OTA („Over-the-Air“).

For additional information please visit

www.klickandshow.com/en



Information and technical data is subject to change without notice.

Features	Klick & Show K-10S Kit	Klick & Show K-10L
TOUCH transmitters (included/optional)	2 / yes, max. 14	- / yes max. 4
HDMI output	up to 4K @ 60Hz (4:4:4)	up to 1080P/WUXGA @ 60Hz
HDMI input (with auto-switching)	up to 4K @ 60Hz (4:4:4)	up to 1080P/WUXGA @ 60Hz
BYOD compatibility	PC/Mac laptops, iOS/Android mobile devices	
Airplay for iOS/MacOS devices	yes	
Wireless video capacity	up to 1080P@30Hz (via TOUCH transmitter), up to 1080P@60Hz (via iOS/Android App, Airplay)	
Simultaneous connections	max. 14	
Wireless access point	IEEE 802.11n/ac with up to 1 Gbps data rate, 2,4/5 GHz frequency band	
Transmission distance	max. 35 m line of sight between TOUCH transmitter and base unit	
Security	AES WPA PSK, WPA2 PSK encryption, Security-level function	
Video/mouse with low latency	yes/yes	
USB-HID function	yes, for touch-control via interactive displays & boards	
Preview windows	yes	
Connectors (base unit)	HDMI out/in, 3.5 mm analog audio out/in, 2x USB 2.0, RJ45 LAN Ethernet with PoE, 12V DC	
Functions	Extended desktop function, Remote-View, Remote-Lock, Remote-Mouse, Wifi-Analyzer, OTA firmware update, Whiteboarding & Annotations, Dual-Network function	
Dimensions (w x d x h)	Base unit: 160 x 105 x 26 mm, without antennas; TOUCH Transmitter: 80 x 60 x 15 mm, USB cable 12 cm	
Weight	Base unit: 450 g with antennas; TOUCH Transmitter: 90 g	
Temperature range	Operation: 0° to +40° C; storage: -20° to +60° C; 20% to 90% humidity, non condensing	
Power supply	12V DC / 2A universal power supply for mains 100-240 V AC, with interchangeable power adaptors type A, C, G, I (for Europe, GB, US, Australia). Alternative PoE (Power-over-Ethernet) via RJ45 port	
Power consumption	Operation (typ.) 10 W; standby 5 W; switched off < 1 W	
Package includes	Klick & Show K-10S base unit, 2x antennas, 2x Klick & Show TOUCH transmitters, mounting brackets, quick-start guide, power supply	Klick & Show K-10L base unit, 2x antennas, mounting brackets, quick-start guide, power supply
Part no.	7488 000 300	7488 000 305